

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO
09/992,597	11/14/2001	Kenji Ose	SIC-00-001-4	3657
7590 08/16/2004		EXAMINER		
DELAND LA	W OFFICE	KIM, CHONG HWA		
P.O. Box 69 Klamath River, CA 96050-0069			ART UNIT	PAPER NUMBER
			3682	
			DATE MAILED: 08/16/2004	

Please find below and/or attached an Office communication concerning this application or proceeding.

(Application No.	Applicant(s)				
	09/992,597	OSE, KENJI				
Office Action Summary	Examiner	Art Unit				
	Chong H. Kim	3682				
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply						
A SHORTENED STATUTORY PERIOD FOR RE THE MAILING DATE OF THIS COMMUNICATIO - Extensions of time may be available under the provisions of 37 CFF after SIX (6) MONTHS from the mailing date of this communication - If the period for reply specified above is less than thirty (30) days, a - If NO period for reply is specified above, the maximum statutory pe - Failure to reply within the set or extended period for reply will, by st Any reply received by the Office later than three months after the m earned patent term adjustment. See 37 CFR 1.704(b).	N. R 1.136(a). In no event, however, ma reply within the statutory minimum o riod will apply and will expire SIX (6) atute, cause the application to becom	y a reply be timely filed thirty (30) days will be considered timely. MONTHS from the mailing date of this communication. e ABANDONED (35 U.S.C. § 133).				
Status						
1) Responsive to communication(s) filed on 1	Responsive to communication(s) filed on 16 June 2004.					
2a)⊠ This action is FINAL . 2b)☐ 1	his action is FINAL . 2b) This action is non-final.					
	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.					
Disposition of Claims						
4)	drawn from consideration.	n.				
Application Papers						
9)☐ The specification is objected to by the Exam	niner.					
10)☐ The drawing(s) filed on is/are: a)☐ accepted or b)☐ objected to by the Examiner.						
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).						
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d). 11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.						
Priority under 35 U.S.C. § 119						
12) Acknowledgment is made of a claim for fore a) All b) Some * c) None of: 1. Certified copies of the priority docum 2. Certified copies of the priority docum 3. Copies of the certified copies of the papplication from the International Bur * See the attached detailed Office action for a	ents have been received. ents have been received in priority documents have be reau (PCT Rule 17.2(a)).	n Application No en received in this National Stage				
Attachment(s)						
1) Notice of References Cited (PTO-892)	4) Tintende	w Summary (PTO-413)				
2) Notice of Draftsperson's Patent Drawing Review (PTO-948)	Paper	No(s)/Mail Date				
3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date 3/12/04 & 6/16/04. 5) Notice of Informal Patent Application (PTO-152) 6) Other:						

DETAILED ACTION

The Examiner acknowledges the applicant's Amendment filed Jun 16, 2004 in response to the Office action made on Jan 12, 2004 and canceling of claims 56-60 and 66-72.

Claim Rejections - 35 USC § 102

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- 2. Claims 34-37, 42-47, and 49-52 are rejected under 35 U.S.C. 102(b) as being anticipated by Higuchi, WO 92/19488.

Higuchi shows, in Figs. 1-6, a bicycle shift control device comprising;

a base member 6b;

an attachment band 6a extending from the base member, wherein the attachment band is structured to surround a handlebar;

a rotatable dial 9 coupled to the base member for rotation coaxially around a rotational axis, wherein the rotatable dial is exposed to the outside;

wherein the rotatable dial is not structured to surround a handlebar so as to rotate coaxially around the handlebar;

a motion limiting structure 22 coupled to the base member and to the rotatable dial that limits a range of rotation of the rotatable dial relative the base member to a predefined arc,

wherein the rotatable dial moves unobstructively within the predefined arc between a cable pulled position and a cable released position;

Page 3

a finger contact projection 8 extending from the rotatable dial in a direction of the rotational axis;

wherein the finger contact projection is structured to prohibit the extension of a finger between all portions of the finger contact projection and the rotatable dial;

wherein the finger contact projection protrudes radially inwardly from a radially innermost outer peripheral surface;

wherein the finger contact projection extends in close proximity to the rotational axis; a shift element coupler 12 disposed with the rotatable dial;

wherein the finger contact projection is coupled to the rotatable dial so that rotation of the finger contact projection correspondingly rotates the rotatable dial to move the shift element coupler and thereby operate the shift control device;

wherein the finger contact projection extends at least partially in a direction perpendicular to the rotational axis;

wherein at least one of the dial and the base member includes a coupling projection 7 for coupling the dial to the base member;

wherein the coupling projection is disposed on the dial and extends into an opening in the base member;

wherein the attachment band has a substantially cylindrical shape;

wherein the attachment band includes a first mounting hole that aligns with a second mounting hole (as shown in Fig. 1);

Application/Control Number: 09/992,597

Art Unit: 3682

wherein the shift element coupler is attached to the rotatable dial;

wherein the shift element coupler is fitted within a coupler bore formed in the rotatable dial;

Page 4

wherein the shift element coupler includes cable end bead receiving opening 13;

wherein the shift element coupler has a substantially cylindrical shape, and wherein the cable end bead receiving opening extends diametrically through the shift element coupler;

wherein the motion limiting structure comprises a motion stop 22 that cooperates with a first limit stop and a second limit stop (as described in the Abstract);

wherein the motion stop extends from the base member; and

wherein the first limit stop and the second limit stop are disposed on the rotatable dial;

wherein the rotatable dial includes a motion limiting groove 23 that forms the first limit stop and the second limit stop (as described in the Abstract);

Claim Rejections - 35 USC § 103

- 3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 4. Claims 34-37, 40, 41, 44, 49-51, 53, are rejected under 35 U.S.C. 103(a) as being unpatentable over Wechsler, U.S. Patent 3,965,763 in view of Higuchi, WO 92/19488.

Wechsler shows, in Figs. 1-3, a bicycle shift control device comprising; a base member 33;

an attachment band (the vertically extended band that partially surrounds the handle 11 as

shown in Fig. 4) extending from the base member;

a rotatable dial 22 coupled to the base member 33 for rotation coaxially around a

rotational axis (bolt 34), wherein the rotatable dial is exposed to the outside;

wherein the rotatable dial is not structured to surround a handlebar so as to rotate

coaxially around the handlebar;

a motion limiting structure 37, 38 coupled to the base member and to the rotatable dial

that limits a range of rotation of the rotatable dial relative the base member to a predefined arc,

wherein the rotatable dial moves unobstructively within the predefined arc between a cable

pulled position and a cable released position;

a finger contact projection 32 extending from the rotatable dial in a direction of the

rotational axis;

wherein the finger contact projection is structured to prohibit the extension of a finger

between all portions of the finger contact projection and the rotatable dial;

wherein the finger contact projection extends in close proximity to the rotational axis;

a shift element coupler disposed with the rotatable dial (column 4, lines 46-50);

wherein the finger contact projection is coupled to the rotatable dial so that rotation of the

finger contact projection correspondingly rotates the rotatable dial to move the shift element

coupler and thereby operate the shift control device;

wherein the finger contact projection extends at least partially in a direction perpendicular

to the rotational axis;

Application/Control Number: 09/992,597

Art Unit: 3682

wherein at least one of the dial and the base member includes a coupling projection 34 for coupling the dial to the base member;

wherein the coupling projection 34 is disposed on the dial and extends into an opening in the base member (see Fig. 4);

wherein the rotatable dial and the finger contact projection are one piece;

wherein the base member includes a cable guide having a cable guide opening for receiving a cable therethrough;

an attachment band extending from the base member 33;

wherein the motion limiting structure comprises a motion stop 38 that cooperates with a first limit stop (gear position number 1) and a second limit stop (gear position number 10);

wherein the motion stop 38 extends from the base member; and wherein the first limit stop and the second limit stop are disposed on the rotatable dial;

but fails to show an attachment band that surrounds a handlebar; the finger contact projection protrudes radially inwardly from a radially innermost outer peripheral surface; and two finger contact surface that faces in the perpendicular direction to the rotational axis and forms a continuous surface with the dial.

As to the matter of the attachment band, Higuchi shows, in Fig. 2, a bicycle shift control device comprising an attachment band 6a extending from a base member 6b, wherein the attachment band is structured to surround a handlebar 1.

It would have been obvious to a person of ordinary skill in the art at the time the invention was made to modify the cumbersome attachment band of Wechsler with the handlebar surrounding attachment band as taught by Higuchi in order to provide a simpler and an easier

method of attaching the shift control device on a bicycle so that a cost of manufacturing can be reduced.

As to the matter of finger contact projection, it would have been obvious to modify the finger contact projection shape of Wechsler by having the projection to protrude radially inwardly from a radially innermost outer peripheral surface and extend the projection so that it forms a continuous surface with the dial, since applicant has not disclosed that having the projection at this specific shape solves any stated problem or is for any particular purpose and it appears that the bicycle shift control device would perform equally well with the finger contact projection at any reasonable shape that would accommodate the fingers to hold and rotate therewith.

5. Claims 54 and 55 are rejected under 35 U.S.C. 103(a) as being unpatentable over Wechsler in view of Higuchi as applied to claims 34, 36, and 37 above, and further in view of White et al., U.S. Patent 3,398,600.

Wechsler in view of Higuchi shows, as discussed above in the rejections of claims 34, 36, and 37, the bicycle shift control device comprising the coupling projection extending into the opening in the base member, but fails to show the coupling projection includes a slot and a locking abutment.

White et al. shows, in Figs. 4 and 5, a rotatable dial 26 comprising a coupling projection 22 having a slot 34 that allows the coupling projection to be compressed and wherein the coupling projection includes a locking abutment 40 facing the rotatable dial 26 for locking the rotatable dial to the base member.

It would have been obvious to a person of ordinary skill in the art at the time the invention was made to modify the coupling projection of Wechsler with the snap-in coupling projection as taught by White et al. in order to provide a simpler design wherein the tolerances between the projection and the receiving end need not be accurately controlled, as described in column 2, lines 1-2 of White et al. so that the cost of manufacturing can be reduced.

Page 8

6. Claims 61-65 are rejected under 35 U.S.C. 103(a) as being unpatentable over Wechsler in view of Higuchi as applied to claim 34 above, and further in view of Knop, U.S. Patent 3,766,793.

Wechsler in view of Higuchi shows, as discussed above in the rejections of claim 34, the bicycle shift control device comprising the finger contact projection, but fails to show the projection extending across substantially an entire diameter, through the rotational axis, and perpendicular to the surface or outer portion of the dial towards the rotational axis of the dial.

Knop shows, in Fig. 1, a gear shift control device 10 comprising a base 22; a rotatable dial 10 coupled to the base member for rotation coaxially around a rotation axis 14, wherein the rotatable dial is exposed to the outside; a finger contact projection 16 extending from the rotatable dial in a direction of the rotational axis; wherein the finger contact projection is structured to prohibit the extension of a finger between all portions of the finger contact projection and the rotatable dial; wherein the finger contact projection extends in close proximity to the rotational axis; a shift element coupler 24 disposed with the rotatable dial;

wherein the finger contact projection extends across substantially an entire diameter of the dial;

wherein the finger contact projection extends through the rotational axis;

wherein the finger contact projection extends diametrically across substantially an entire diameter of the dial;

wherein the finger contact projection extends from a surface of the dial that is generally perpendicular to the rotational axis;

wherein the finger contact projection extends from an outer portion of the dial towards the rotational axis.

It would have been obvious to a person of ordinary skill in the art at the time the invention was made to modify the dial of Weschler with the dial having the vertically extending finger contact projection as taught by Knop in order to provide a more ergonomic knob that can be turned with more ease.

Response to Arguments

- 7. Applicant's argument with respect to the rejection under 35 USC 102(b) by Higuchi have been considered but is most in view of the new ground(s) of rejection. (Note: the finger contact projection now is the element 8).
- 8. Applicant's argument with respect to the rejection under 35 USC 103(a) by Wechsler have been considered but is moot in view of the new ground(s) of rejection.

Conclusion

Page 10

9. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Chong H. Kim whose telephone number is (703) 305-0922. The examiner can normally be reached on Tuesday - Friday; 8:00 - 6:00.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David A Bucci can be reached on (703) 308-3668. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Application/Control Number: 09/992,597 Page 11

Art Unit: 3682

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

chk

August 10, 2004

PRIMARY EXAMINER